İnci Transformatör Aksesuarları

San.ve Tic. A.Ş.

- TAP CHANGER
- BIMETAL THERMOMETERS
- PRESSURE SAFETY VALVE
- OIL LEVEL INDICATOR
- HERMETIC RELAYS
- MOISTURE HOLDERS
- TRANSFORMERS METAL PARTS
- BUSHING PARTS

www.inctransfo.com

TAP CHANGER



Type : IHR
Voltage (A) : 16-20-30
Current (kV) : 10-30-63
Number of Positions : 2.....7
Connection : Delta-Star-
Series parallel-Common output per phase



Type : IHZ
Voltage (A) : 20-30
Current (kV) : 30-63-120
Number of Positions : 2.....11
Connection : Delta-Star-
Series parallel-Common output per phase



Type : IHH
Voltage (A) : 20-30
Current (kV) : 30-63-120
Number of Positions : 2.....11
Connection : Delta-Star-Series parallel-Common output per phase



Type : IHH
Voltage (A) : 20-30-60
Current (kV) : 150-600
Number of Positions : 2.....11
Connection : Delta-Star-
Series parallel-Common output per phase



Type : IHFII
Voltage (A) : 20-30-60
Current (kV) : 400-600
Number of Positions : 2.....6
Connection : Delta-Star-
Series parallel-Common output per phase



Type : IHFIV
Voltage (A) : 20-30-60
Current (kV) : 800-1200
Number of Positions : 2.....6
Connection : Delta-Star-
Series parallel-Common output per phase

www.inctransfo.com

THERMOMETERS



Bimetal Thermometers

Type : BOT 15
Code No : 210-220-230
Connections : R1"-R3/4"-R1/2"
Norm : (DIN 16160-PART2)

These types can also be manufactured without contacts or changeover contact



Machine Glass Thermometers

Type
Code No : Gt63 - Gt100
Probe lenght "L" : 63 - 100
Working liquid : Alcohol
Working limit : 0 - 130°C
Connections diameter : R1/2"
Pocket diameter : 12 mm



Liquid Filled Thermometers

Type
Nominal size : 100
Measuring range : -30+60° / 0+120°C / 0+160°C / 0+500°C
Electrical Contact : Without electrical contact

www.inctransfo.com

PRESSURE SAFETY VALVES



Type : BAV80
Code No : 430-
Control system : Mechanical
Working pressure range : 0,30 – 0,85 kg/cm²



Type : PSV50
Code No : 470-
Control system : R1½ " – R2 "
Working pressure range : 0,30 – 0,85 kg/cm²





Type : BAV10
Code No : 410-
Control system : R1" – R1½ "
Working pressure range : 0,30 – 0,85 kg/cm²



Type : PSV10
Code No : 401-
Control system : R½" 14NPT
Working pressure range : 10 psig

www.inctransfo.com

MANGETIC OIL LEVEL INDICATOR

(without contact)



Type : OLCA-B0 - OLCA-B1 - OLCA-B2
Code No : 310-00 - 310-01 - 310-02
Number of contacts : 0 - 1 - 2
Transformer capasity : >5000 kVA
Working range : -25°C + 80°C
Norm : FORM B (DIN 42569) – EN 50516-5

MOISTURE HOLDERS



Type : HK 0,15 - 0,25 kg
Code : 620



Type : HK 0,5 kg FORM A
Code : 620A



Type : HK 0,5 kg FORM B
Code : 620B



Type : HK 0,5 kg FORM C
Code : 620C

www.inctransfo.com



İnci Transformatör Aksesuarları
San.ve Tic. A.Ş.

CONTACT US

Phone:
+90 539 106 65 43
+90 216 999 22 57

Mail:
inc.elk@outlook.com.tr
sales@inctransfo.com

Address:
Çınardere Mh. Çapalık Sk.
No:18 Pendik/İstanbul, TÜRKİYE



HERMETIC RELAYS



Type : HPR-L (LONG)
Nominal size : 720



Type : HPR-L (SHORT)
Nominal size : 710



METAL ACCESSORIES

THERMOMETERS CASE

Type	:	TEF			
Code no	:	TCS-610	TCS-611	TCS-630	TCS-631
Capacity/Size	:	5 l	8 l	8 kg	8 kg



Type :
SINGLE / DOUBLE FLANGES
BALL VALVE

OIL DRAINING DEVICES



Type	:	NW22	NW31	NW40
Code no	:	NW22-00	NW31-00	NW40-00
Form Transformers	:	Above 80 to 1600 kVA		
Norm	:	DIN 42551		





İnci Transformatör Aksesuarları
San.ve Tic. A.Ş.

www.inctransfo.com